








## Responsibility and recognition



**Performing competent authority:**  
Julius Kühn-Institute (Germany)  
Institute for Application Techniques in Plant Protection  
Messeweg 11-12  
D-38104 Braunschweig

### This test is recognized by the ENTAM members:

	<b>BLT</b> - Francisco Josephinum, Wieselburg (Austria)	007/11
	<b>Cemagref</b> - Institut de recherche pour l'ingénierie de l'agriculture et de l'environnement (France)	CEMAGREF/ENTAM/11/026
	<b>HIAE</b> Hungarian Institute of Agricultural Engineering (Hungary)	D-42/2011
	<b>ENAMA</b> Ente Nazionale per la Meccanizzazione Agricola (Italy)	ENTAM „Rapporto di prova prestazionale“ 5/2011
	<b>PIMR</b> - Przemyslowy Instytut Maszyn Rolniczych Industrial Institute of Agricultural Engineering (Poland)	PIMR - 59/ENTAM/11
	<b>CMA</b> Generalitat de Catalunya Centre de Mecanització Agrària (CMA) (Spain)	EB 002/11
	<b>NAGREF</b> National Agricultural Research Foundation (Greece)	AE/145/01/ZZ



## ENTAM - Test Report



Trade mark:	Agrotop
Model:	AirMix 110-01
Equipment type:	hydraulic nozzle, flat spray
Field of application:	Field crop spraying
Pressure range:	2 - 6 bar tested
Standard working height:	50 cm

**Manufacturer:**  
Agrotop GmbH  
Köferinger Str. 5  
93083 Obertraubling  
Germany

Apr 2011

**Test report: D - 1914**

### Test results

This nozzle has been tested without accessories.  
This nozzle is appropriate for the use of spraying field crops, grassland, vegetables and ornamental plants with a liquid pressure of 2.0 - 6.0 bar.

The front page image of this report shows the demountable nozzle parts (right side) and the assembled nozzle in a 90° twisted position (left side).

The nozzle is a flat spray nozzle with air injector. The body and orifice is made from plastic.

- The cross distribution CV<sup>1)</sup> is between 6.4 % (4 bar) and 8.9 % (2 bar) for the tested pressure range 2.0 - 6.0 bar at a standard working height of 50 cm. For a pressure of 4.0 bar, the CV varies from 3.7 % (40 cm) to 6.4 % (50 cm). The maximum allowed CV for one working height and one pressure (specified by the manufacturer) is 7 %, for all heights and pressures is 9 %.
- The deviation between the measured single nozzle flow rate and the flow rate table is between -1.1 % (at 3 bar) and 3,4 % (at 4 bar). The maximum allowed deviation is 5 %.
- The max. deviation of the single nozzle flow rates from the mean flow rate is between 1.3 % and 2.1 %.
- The nozzle fulfils the discharge rate requirement of the color code according ISO 10625 (color code: orange, 0,4 l/min at 3 bar). See tab.1.

### Test results

Pressure (bar)	Discharge rate without accessories (l/min)	droplet size <sup>2)</sup>
2.0	0,33	coarse
4.0	0,47	coarse
6.0	0,57	fine

tab.1: Discharge rate and droplet size depending on liquid pressure.

- 1) on a spray boom with 50 cm nozzle distance
- 2) according BCPC scheme (additional information)

### Additional information

*The tested nozzles (24) were picked out at random of a stock of 200 nozzles. Testing takes place according to the Technical Instructions for ENTAM-Tests of Spray nozzles, rel.1.*

*This procedure was developed by the competent testing authorities of the European countries participating in ENTAM and is based on the ISO 5682 standard: „Equipment for crop protection - Spraying equipment; Part 1 Test methods for sprayer nozzles“ and on EN 12761 standard: „Agricultural and forestry machinery - Sprayers and liquid fertilizer distributors - Environmental protection; Part 2“. This test is only a technical performance test which takes place without an accompanying field test. The test results apply only to the tested appurtenances of the sprayer. Statements on the behaviour of different appurtenances cannot be derived from these results.*

Free download of the test report under: [www.ENTAM.net](http://www.ENTAM.net)  
or: [www.jki.bund.de](http://www.jki.bund.de)