



TEST REPORT

of the
Julius Kühn-Institut
Federal Research Institute
for Cultivated Plants, Braunschweig



Offcenter flatfan nozzle Agrotop AirMix OC 80-03
(plastic, blue) in combination with Agrotop AirMix 110-04 or
Agrotop AirMix NoDrift 110-04 or Agrotop TurboDrop HiSpeed 110-
04 or ALBUZ CVI Twin 110-04 or ALBUZ AVI Twin 110-04 or
ALBUZ AVI 110-04

**Approved for spraying field crops
used at the end of the spray boom**

Applicant and Manufacturer
Agrotop GmbH
Köferinger Strasse 5
93083 Obertraubling-Gebelkofen

Approved on
6 January 2011
Extension of approval
on 15 January 2015

Assessment

The offcenter flatfan nozzle Agrotop AirMix OC 80-03 (plastic, blue) was tested without accessories. The nozzle is suitable for spraying field crops, provided that the following technical requirements are fulfilled:

1. Usage of the nozzle at the end of the spray boom in combination with Agrotop AirMix 110-04 or Agrotop AirMix NoDrift 110-04 or Agrotop TurboDrop HiSpeed 110-04 or ALBUZ CVI Twin 110-04 or ALBUZ AVI Twin 110-04 or ALBUZ AVI 110-04,
2. Installation in a spray boom with a sufficient and a steady amount of liquid flow,
3. 500 mm nozzle spacing,
4. 50 – 75 cm between nozzles and spray target (consistency of evenness of cross distribution proved satisfactory at a distance range from 40 cm to 90 cm),
5. Spray pressure – measured in front of the nozzle – between 1.0 and 8.0 bar; liquid volume flow per nozzle as stated in table below.

Suitable precautions should be taken to assure that the nozzles do not get blocked up or drip when in use. The dimensions of the nozzle tip comply with standard ISO 8169. The colour coding comply with standard ISO 10625. When using the edge nozzle the regulations for use (pressure range and target surface distance) of the respective main nozzle must be observed.

Pressure (bar)	Liquid flow volume without accessories (l/min)	Max. deviation of single nozzle flow from the dosage tables	Droplet spectrum (BCPC-Standard)
1.0	0.72	4.59 %	very coarse
2.0	1.01	4.02 %	very coarse
3.0	1.24	-	very coarse
4.0	1.43	2.98 %	coarse
5.0	1.60	-	coarse
6.0	1.76	3.59 %	coarse
7.0	1.88	-	-
8.0	2.03	-	-

Basics for testing

The tests were carried out on basis of the Regulations for Testing Plant Protection Equipment (JKI-Guideline 2-1.1:2013) and of ISO 5682-1:1999. The requirements of ISO 16119-2:2013 and of JKI-Guideline 1-2.1:2013 were fulfilled.

Loss reducing properties

Included in the list „Loss reducing equipment“ (as of 23 March 2015)

Drift reducing classification	Type of equipment and drift reducing parts	Regulations for use
50 %	Fieldsprayers with Agrotop AirMix 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 2.0 bar, nozzle height above target 50 cm
50 %	Fieldsprayers with Agrotop AirMix NoDroft 110-04 in combination with Agrotop AirMix OC 03	Nozzle height above target 50 cm
50 %	Fieldsprayers with Agrotop TurboDrop HiSpeed 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 6.0 bar, nozzle height above target 50 cm
50 %	Fieldsprayers with ALBUZ AVI 110-04 in combination with Agrotop AirMix OC 03	Nozzle height above target 50 cm
50 %	Fieldsprayers with ALBUZ AVI Twin 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 4.0 bar, nozzle height above target 50 cm
75 %	Fieldsprayers with Agrotop AirMix 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 1.0 bar, nozzle height above target 50 cm
75 %	Fieldsprayers with Agrotop AirMix NoDrift 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 2.5 bar, nozzle height above target 50 cm
75 %	Fieldsprayers with Agrotop TurboDrop HiSpeed 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 3.0 bar, nozzle height above target 50 cm
75 %	Fieldsprayers with ALBUZ AVI 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 3.0 bar, nozzle height above target 50 cm
75 %	Fieldsprayers with ALBUZ CVI Twin 110-04 in combination with Agrotop AirMix OC 03	Nozzle height above target 50 cm
75 %	Fieldsprayers with ALBUZ AVI Twin 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 2.5 bar, nozzle height above target 50 cm
90 %	Fieldsprayers with Agrotop TurboDrop HiSpeed 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 2.0 bar, nozzle height above target 50 cm
90 %	Fieldsprayers with ALBUZ CVI Twin 110-04 in combination with Agrotop AirMix OC 03	First 20 m from field edge spraying with max. 1.5 bar, nozzle height above target 50 cm

Field testing:

-

Technical testing:

Institut für Anwendungstechnik im
Pflanzenschutz des
Julius Kühn-Instituts,
Messeweg 11-12,
38104 Braunschweig © JKI, July 2015