



TEST REPORT

of the
Julius Kühn-Institut
Federal Research Institute
for Cultivated Plants, Braunschweig



**Double - Flatfan nozzle AITTJ60–110 06 VP
(Plastic, grey)**

Approved for spraying field crops

Applicant
TeeJet Technologies GmbH
Paul-Strähle-Straße 10
73614 Schorndorf

Manufacturer
Spraying Systems Co.
North Ave at Schmale Rd.
Wheaton, IL (USA)

Approved on
8. Januar 2020

Assessment

The double-flatfan nozzle TeeJet AITTJ60–110 06 VP (Plastic, grey) was tested without accessories. The nozzle is suitable for spraying field crops, provided that the following technical requirements are fulfilled:

1. Installation in a spray boom with a sufficient and a steady amount of liquid flow,
2. 500 mm nozzle spacing,
3. 50 cm between nozzles and spray target (consistency of evenness of cross distribution proved satisfactory at a distance range from 40 cm to 60 cm),
4. Spray pressure – measured in front of the nozzle – between 1.5 and 6.0 bar; liquid volume flow per nozzle as stated in table below.

Suitable precautions should be taken to assure that the nozzles do not get blocked up or drip when in use. The dimensions of the nozzle tip comply with standard ISO 10626. The colour coding of the nozzle comply with standard ISO 10625.

Pressure (bar)	Liquid flow volume without accessories (l/min)	Max. deviation of single nozzle flow from the dosage tables	Evenness of cross distribution at (cm) 40 / 50 / 60 (Vk %)	Droplet spectrum (ISO 25358)
1.5	1.71	-	5.9 / 4.0 / 2.2	ultra coarse
2.0	1.97	3.70 %	- / 3.0 / -	extreme coarse
3.0	2.42	3.67 %	5.4 / 2.4 / 2.5	extreme coarse
4.0	2.79	3.42 %	- / 2.5 / -	very coarse
5.0	3.12	-	- / 2.5 / -	very coarse
6.0	3.42	3.11 %	- / 2.7 / -	very coarse

Loss reducing properties

Included in the list „Loss reducing equipment“ (9 April 2020)

Drift reducing classification	Type of equipment and drift reducing parts	Regulations for use
75 %	Fieldsprayers with nozzle TeeJet AITTJ60 110 06 VP	First 20 m from field edge spraying with max. 6.0 bar, nozzle height above target 50 cm.
90 %	Fieldsprayers with nozzle TeeJet AITTJ60 110 06 VP	First 20 m from field edge spraying with max. 2.0 bar, nozzle height above target 50 cm.

Field test

The nozzles were used in the year 2018 together with puls width modulation System “DynaJet” on a total of 633 hectares, a sufficient effect of the plant protective measures was confirmed.

Basics for testing

The tests were carried out on basis of the Regulations for Testing Plant Protection Equipment (JKI-Guideline 2-1.1:2013) and of ISO 5682-1:1999. The requirements of ISO 16119-2:2013 and of JKI-Guideline 1-2.1:2013 were fulfilled.

Field testing:

-

Technical testing:

Institute for Application Technique in
Plant Protection
Messeweg 11-12,
38104 Braunschweig

© JKI, März 2021